

Improvements to the U.S. Army Research Laboratory (ARL) Army Unit Resiliency Analysis (AURA) "All Clear" Algorithm

Richard L. zum Brunnen

ARL-TR-978 March 1996

19960318 049

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

DATO CATALLE DESTRUCTO F

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
Public reporting burden for this collection of infi- gathering and maintaining the data needed, and collection of information, including suggestions	f completing and reviewing the collection of inf	ormation. Send comments regarding this I	ourden estimate or any other aspect of this
Davis Highway, Suite 1204, Artington, VA 22202 1. AGENCY USE ONLY (Leave blan	4302, and to the Office of Management and Bu	adget, Paperwork Reduction Project(0704-0	rt88), Washington, DC 20503.
,	March 1996	Final, April - Jul	v 95
4. TITLE AND SUBTITLE			5. FUNDING NUMBERS
Improvements to the U.S. A		ARL) Army Unit	
Resiliency Analysis (AURA) "All Clear" Algorithm		665604
6. AUTHOR(S)			7
Richard L. zum Brunnen			
7. PERFORMING ORGANIZATION N	IAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION
U.S. Army Research Labora	tory		REPORT NUMBER
ATTN: AMSRL-SL-CM			Ans em 050
Aberdeen Proving Ground, I	VID 21010-5423		ARL-TR-978
9. SPONSORING/MONITORING AGI	ENCY NAMES(S) AND ADDRESS(E	S)	10.SPONSORING/MONITORING
			AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY	STATEMENT		12b. DISTRIBUTION CODE
122. DISTRIBUTIONAVAILABILITE			125. SISTRIBOTION COSE
Approved for public release;	distribution is umlimited.		
13. ABSTRACT (Maximum 200 word	ls)		
The Project Manager for	r the Corps Surface-to-Air	Missile (PM CORPS SA	M) is planning to use the U.S. Army
			del to assess the weapon system's
• •	•	• • •	RA by PM CORPS SAM's contractor
MEVATEC. This report is	a result of the review of M	MEVATEC's "All Clear"	algorithm used in determining when
personnel can remove mission	on-oriented protective postur	re (MOPP) gear.	
14. SUBJECT TERMS			15. NUMBER OF PAGES
AURA, MOPP, "All Clear," chemical, algorithm			18 16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICAT OF ABSTRACT	ION 20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL

TABLE OF CONTENTS

		Page
1.	INTRODUCTION	1
2.	OBJECTIVE	1
3.	APPROACH	2
4.	SCOPE	` 2
5.	PROBLEM	3
6.	SOLUTION	4
7.	CONCLUSION/RECOMMENDATION	6
	APPENDIX A: ARL'S ORIGINAL CLDTIM.f SUBROUTINE	7
	APPENDIX B: MEVATEC'S CLDTIM.f SUBROUTINE	11
	DISTRIBUTION LIST	17

1. INTRODUCTION

The Ballistic Missile Defense Organization, in its 1994 Report to Congress, noted the following:

Currently, mature design Theater Ballistic Missiles (TBMs) are extensively deployed, and, because of their low cost and availability, they are proliferating throughout the world. . . . Adding to the threat complexity are the various warheads including high explosives, bulk or submunitions, and weapons of mass destruction (nuclear, biological, and chemical). The TBM allows the enemy, who formerly had to fly over the intended target in order to deliver their payload, to stand off at a safe range of hundreds of kilometers. Desert Storm demonstrated the difficulty of identifying an incoming TBM as a simple unitary high explosive payload or a weapon of mass destruction/casualty. An unengaged weapon of mass destruction would have far more devastating effects than even the tragic loss of life seen in the military barracks near Dhahran [Saudi Arabia]. How devastating would an engaged TBM-delivered weapon of mass destruction have been? The more relevant question to the air defense material developer is 'How lethal does my defense weapon have to be?'

Current air defense Operational Requirement Documents (ORDs) require the highest interceptor lethality possible, partly due to the current inability to reliably estimate the effects on defended assets from partially destroyed payloads, and high lethality requirements drive up interceptor complexity and cost.

To date, extensive work has been done to determine Pk contours and end game environments, etc. However, little effort has been expended to relate the defended asset dynamic effectiveness against various weapon delivery systems and payloads to the air defense system performance.

The cooperative analysis of lethality and mission effectiveness, funded by Project Manager for the Corps Surface-to-Air Missile (PM CORPS SAM), will provide a means to evaluate the defense mission effectiveness for interceptors of varying lethality, deployment strategies for assets and defense components, and engagement strategies for weapon systems.

2. OBJECTIVE

The objective of the PM CORPS SAM-funded work is to provide a common basis for determining the lethality requirements for the Medium Extended Air Defense System (MEADS). MEVATEC Corporation, a contractor to PM CORPS SAM, has been running the Army Unit Resiliency Analysis (AURA) program for several years. During this time MEVATEC has also been modifying source code

to address the company's specific problems. One of the portions of AURA code which MEVATEC modified was the "All Clear" algorithm. This is the algorithm that deals with the problem of vapor cloud drift and assesses when personnel can revert to their original mission-oriented protective posture (MOPP). The objective of this task was to review both the original Army Research Laboratory (ARL) algorithm and the modified MEVATEC algorithm and then to recommend any changes that ARL felt were necessary.

3. APPROACH

A methodology that links a force engagement simulation in a serial fashion with a lethality, atmospheric/ground transport, and unit effectiveness will be used to evaluate the dynamic effectiveness of the defended asset as a function of defense mission effectiveness. The Naval Surface Warfare Center (NSWC) Vapor, Liquid, Solid Tracking (VLSTRACK) agent transport simulation and the AURA computer simulation model, developed by ARL, and the Submunition Laydown Pattern Predictor (SLPP) propagation model will form the basis for this linkage.

4. SCOPE

The implementation of this methodology will require modifications to the AURA model and general support for questions that arise. MEVATEC, PM CORPS SAM's contractor, will modify the AURA code, with ARL acting as consultants.

This task involves the review of the updated "All Clear" algorithm within AURA. The AURA All Clear algorithm was modified to account for cases with large (with respect to asset size) vaporous agent clouds (i.e., primarily dosage with little or no deposition). In these cases, it was found that the original algorithm gave an unrealistically early "all clear" to come out of mission-oriented protective posture, level 4 (MOPP IV). The problem grew when effects of this shortfall were included. ARL was tasked to review the modifications made to the algorithm, assess the validity, and provide a report on the assessment with recommended changes if necessary.

5. PROBLEM

MEVATEC Corporation's modifications to the original ARL Survivability/Lethality Analysis Directorate (SLAD)/Ballistic Vulnerability/Lethality Division (BVLD) All Clear algorithm are confined to finding the largest extent of the threat cloud and then setting the XTENT variable to the greater of the two (largest extent of the unit or the largest extent of the threat cloud). The largest extent is then used to calculate TDRFT—the maximum time, in minutes, which might be required for the toxic cloud to drift across the unit. TDRFT is found by dividing XTENT by the windspeed (with units of meters per minute). XTENT has units of meters, and TDRFT has units of minutes.

The All Clear algorithm is coded in the CLDTIM.f subroutine. ARL's original version of this subroutine can be found in Appendix A, and MEVATEC's modified version of this routine can be found in Appendix B.

It needs to be noted that in MEVATEC's additions to the CLDTIM.f subroutine, where XTENT and TDRFT are calculated, a search is performed on the x and y arrays of the cloud grid Cartesian coordinates (XVPR and YVPR). The maximum and minimum corresponding x and y coordinates are determined. The Pythagorean theorem is then used to find the length of the diagonal that connects these points (XTENTV). What is important here is that these calculations are based solely on the rectangular Cartesian coordinates of the cloud grid only. During this procedure, there is no accounting for cloud values of zero within the grid. Clouds usually take on an elliptical shape as the material is transported downwind. The orientation of this elliptical shape is with the major axis following the wind direction. The elliptical cloud is characterized by a two-dimensional rectangular grid. The diagonal (XTENTV) is the distance that the opposite corners of the full rectangular grid are from one another. A good percentage of the distance may be over areas where the cloud measure value is zero and where much of the area will never be affected by the cloud.

As far as the past use of the All Clear signal when dealing with liquid agents goes, during SLAD's study of the Corps Main Command Post (CMCP) performed in FY94, the assumption was made that the minimum time for the All Clear, from liquid agent, to be declared was a minimum of 30 min plus the evaporation time of the agent (or persistence time). Doctrine calls for at least two negative testing procedures with the M8 chemical agent detection paper to have taken place. The time required to

complete a testing procedure, again according to doctrine, is 15 min, and with two sweeps required, a minimum of 30 min total was used.

6. SOLUTION

A better approximation for the maximum extent of a cloud which will have to transverse the unit area is simply the maximum downwind (x direction) length of the cloud. Using the diagonal not only artificially inflates this distance by using the areas of zero cloud effect, but it also seems to assume that the wind direction can vary—hence, the crosswind component used to create the diagonal. Currently, the wind direction and speed are fixed throughout the analysis. The wind speed is one of the major driving factors behind the transport and diffusion of the cloud. In the case of the cloud being larger than the asset, the only time the cloud extent is used, there are two possible cloud/unit configurations when the agent source occurs upwind of the asset:

- (1) The cloud does not overlap the asset, and
- (2) The cloud does overlap the asset.

When the cloud does not overlap the asset, the maximum distance that the cloud may have to travel to clear the unit is the maximum distance across the unit with respect to the wind direction (let's call this "UNITWMAX") plus the maximum of the cloud downwind length (XTENTV) and the downwind distance that the initial source of the cloud (referred to as the "start" of the cloud) is from the upwind edge of the unit (let's call this "CLDOFF").

When the cloud does overlap the asset, the maximum distance a cloud may have to travel to clear the unit is UNITWMAX plus CLDOFF.

One should realize that "large" aerosol or vapor clouds tend to be much longer than they are wide. The longest linear distance covered by the cloud can generally be found along its center line (with respect to the wind direction). If one makes the assumption that PRETOX has bounded the cloud such that the first and last x coordinates of the cloud grid are where the cloud begins and ends, one can develop an algorithm, very similar to that of MEVATEC's, to calculate the maximum extent of the cloud. The array containing the cloud measure grid needs to be accessible to the CLDTIM.f subroutine; this array is

contained in the TOXRNRM common block under the variable name VPRNR. The array containing the asset coordinates is already accessible to the CLDTIM.f subroutine; this array is contained in the CULL common block under the variable name DEPMAX. The array containing the munition impact point coordinates also needs to be accessible to the CLDTIM.f subroutine; this array is contained in the EMPLOY common block under the variable name DGZ. The wind angle variables (ANGWND, COSWND, and SINWND) are members of the WNDANG common block; this also needs to be accessible to the CLDTIM.f subroutine. Also, an assumption central to the construction of the algorithm present is that the asset center is the origin of the Cartesian coordinate system (the zero-zero point), the asset is symmetrical about the origin, and the general shape of the asset is either square or rectangular. The algorithm could be written as follows:

- (1) Find the "start" of the cloud (minimum x and corresponding y). Find the y value for the maximum cloud effect value in the first x line of the cloud grid VPRNR.
- (2) Find the "end" of the cloud (maximum x and corresponding y). Find the y value for the maximum cloud effect value in the last x line of the cloud grid VPRNR.
- (3) Use Pythagorean's theorem and the points found in 1 and 2 to find the total extent (XTENT) of the cloud.
 - (4) Find the total extent of the asset with respect to the wind direction (UNITWMAX).
 - Determine the angle the unit diagonal makes with the x axis (ANGDIA).
 ANGDIA = INV TAN(DEPMAX(2,2)/DEPMAX(1,2)).
 - If (ANGDIA \geq ANGWND), then UNITWMAX = 2*(DEPMAX(1,2)/COSWND).
 - ELSE (ANGDIA < ANGWND) then UNITMAX = 2*(DEPMAX(2,2)/(SINWND)).
- (5) Find the maximum downwind distance that the "start" of the cloud is from the upwind edge of the unit (CLDOFF). Do for all incoming rounds and pick the one which is the largest.

- X(I) is the x coordinate of the impact of round I.
- Y(I) is the y coordinate of the impact of round I.
- The downwind distance from the impact point to the asset center is DOWND. DOWND = X(I)*COSWND + Y(I)*SINWND.
- The downwind distance from the impact point to the asset edge is DOWNA. DOWNA = DOWND - (0.5*UNITMAX).
- The downwind distance from the "start" of the cloud to the edge of the asset is CLDAD. The
 XX(MIN) is the minimum x found in 1; this is the distance from the round function point to
 the "start" of the cloud (cloud ground touch down). CLDAD = DOWNA XX(MIN).

7. CONCLUSION/RECOMMENDATION

A review of the updated All Clear algorithm within AURA has been completed by ARL. While the modifications made by MEVATEC were found to be valid, ARL recommends that a more robust algorithm be developed.

APPENDIX A:

ARL'S ORIGINAL CLDTIM.f SUBROUTINE

```
SUBROUTINE CLDTIM
 2
            THIS SUBROUTINE DEALS WITH THE PROBLEM OF VAPOR CLOUD DRIFT.
            THE TIME REQUIRED FOR TOXIC VAPOR TO DRIFT ACROSS THE LONGEST LENGTH
            OF THE UNIT IS CALCULATED;
                                         TIME = LENGTH OF UNIT/VELOCITY OF WIND.
            THIS TIME VALUE IS USED IN THE CALCULATION OF THE
            'PERSISTENCE TIME'. PERSISTENCE TIME IS USED HERE TO REFER
            TO THE LENGTH OF TIME THAT A TOXIC HAZARD REMAINS IN THE UNIT
 8
            AREA. PERSONNEL DO NO REVERT TO ORIGINAL MOPP POSTURE
            UNTIL SOME TIME AFTER THE 'PERSISTENCE' TIME HAS ELAPSED.
10
11
12
               COMMON/CULL/LCULL(2), DEPMAX(2,2), DELMAX(@NWP), TLEMAX
               COMMON/IO/ IM5, IM6
13
               COMMON/LTHTYP/ LCNV, LNUKE, LNUCDN, LTOX, LTOXDN, LNUCDS, LTOXDS,
15
         c smart
16
              + LSMART
17
               LOGICAL LTOX
18
               COMMON/RECOOP/ NRECT, TIMGAP, TRECUP(@TIM), TRECON(@TIM)
19
               COMMON/TALLY/ NREC, TALTIM (@TIM), LNKWKT (@TIM), LCHNST (@TIM),
20
              + EFFREC (@TIM)
               COMMON/TOXTRM/XTRC(@TW,2),YTRC(@TW,2),XTRP(@TW,2,2),YTRP(@TW,2,2),
22
              + XTRV(@TW,2,2),YTRV(@TW,2,2),CTMIN(@TW),CTMAX(@TW),TOXWND(@TW),
23
              + CNCXT(@TW), CNCX(@TW), CNCY(@TW), CNCTP(@TW)
               COMMON/TXCLTH/NTXWPN, NXCNTM(@TW), NTVPR(@TW), NXVPR(@TW), NYVPR(@TW),
24
              + NDXTX(@TW,4),XCNTM(@TW,@XTC),TVPR(@TW,10),XVPR(@TW,@XTW),
25
26
              + YVPR(@TW,@YTW),EVPTMX(@TW),PRSTIM(@TW),NYCNTM(@TW),
27
              + YCNTM(@TW,@YTW)
28
            DETERMINE THE DRIFT TIME OF THE TOXIC CLOUD
29
            AND ADD THIS TO THE PERSISTENCE TIME GIVEN BY NUSSE (TIME FOR
30
31
            AVERAGE DROPLET TO EVAPORATE.)
32
            TIME FOR CLOUD TO DRIFT DOWNWIND OF UNIT IS CALCULATED BASED ON
33
         С
34
            THE RELATIONSHIP: DISTANCE = VELOCITY * TIME.
            TDRFT = MAXIMUM LENGTH OF UNIT/VELOCITY OF WIND.
35
36
            TDRFT IS TIME FOR CLOUD TO DRIFT DOWNWIND OF UNIT.
37
38
         С
            LTOX IS LOGICAL SIGNIFYING WHETHER OR NOT THIS IS A TOXIC SCENARIO.
            IF THIS IS A TOXIC SCENARIO THEN DO THE FOLLOWING CALCULATION:
39
40
        C
41
               IF ( LTOX ) THEN
42
        С
            CALCULATE MAXIMUM LENGTH OF THE UNIT BASED ON PYTHAGOREAN THEOREOM.
43
        С
44
            DEPMAX IS ARRAY OF MAXIMA AND MINIMA DEPLOYMENT POINTS.
           DEPMAX(1,2) IS THE MAXIMUM VALUE DEPLOYMENT POINT ALONG X AXIS.
45
        С
46
            DEPMAX(1,1) IS THE MINIMUM VALUE ALONG THE X AXIS.
           DEPMAX(2,2) IS THE MAXIMUM VALUE ALONG THE Y AXIS.
47
           DEPMAX(2,1) IS THE MINIMUM VALUE ALONG THE Y AXIS.
48
49
        С
           XTENT IS THE LARGEST EXTENT OF THE UNIT ACROSS WHICH
50
        С
51
           A TOXIC CLOUD MIGHT TRAVEL
52
        С
53
                  XTENT = SQRT ( (DEPMAX(1,2)-DEPMAX(1,1))**2 +
54
                   (DEPMAX(2,2)-DEPMAX(2,1))**2)
55
        С
                  DO 24 K = 1, @TW
56
                  IF ( TOXWND (K) .GT. 0.01 ) THEN
57
58
        С
59
           MULTIPLY TOXWIND BY 60 TO CONVERT FROM SECONDS TO MINUTES.
           MINUTES = METERS/[(METERS/SECOND)(60 SECONDS/MINUTE)].
60
61
62
                     TDRFT = XTENT / (TOXWND(K)*60.)
63
64
           IF WIND SPEED IS CLOSE TO ZERO, THEN THERE IS NO DRIFT DOWNWIND,
           SO TDRFT IS SET CLOSE TO INFINITE. CLOUD WON'T DRIFT DOWNWIND
65
           AND PERSONNEL WILL BE FORCED TO STAY IN MOPP UNTIL EVAPORATION
66
           OF AGENT. THIS IS VALID FOR THE PERSISTENT AGENT CASE, BUT
67
           NOT FOR A NONPERSISTENT AGENT. A CHECK AND CORRECTION IS
68
           MADE FOR THIS LATER.
69
70
        C
```

ELSE

```
TDRFT = 1.E35
 72
 73
                    ENDIF
 74
              TDRFT IS THE TIME - IN MINUTES - TO DRIFT ACROSS THE
 75
 76
              LARGEST EXTENT OF THE UNIT.
 77
              PRSTIM CONTAINS THE TIME OF THE FIRST DOSAGE GRID TO
 78
              SHOW NO INCREASES. FOR A PURE LIQUID (NO VAPOR) IT IS 0.
 79
             IF EVERY GRID SHOWED AN INCREASE, IT IS 1.E35. (THE AURA ANALYST MUST BE CAREFUL WHEN CHOOSING NUSSE INPUT
 80
 81
              TIMES TO AVOID MODELING AN 'INFINETELY' PERSISTENT
 82
              HAZARD AS A RESULT OF SELECTING TIMES WHICH ARE
 83
              NOT REPRESENTATIVE OF THE LIFETIME OF THE HAZARD.
 84
 85
              TOTAL PERSISTENCE TIME IS ESTIMATED BY TAKING THIS
 86
              MAXIMUM EVAPORATION TIME AND ADDING THE DRIFT TIME TO IT
 87
              TO ACCOUNT FOR THE SECONDARY EVAPORATION HAZARD OF LIQUID
 88
          C
              AGENT. HOWEVER, THERE IS NO SECONDARY VAPOR HAZARD FOR PURELY
 89
              VAPOR AGENTS.
 90
 91
 92
              TO CALCULATE TOTAL PERSISTENCE TIME....
 93
 94
             FOR A LIQUID AGENT:
              ADD EVPTMX, THE EVAPORATION TIME OF A LIQUID AGENT,
 95
          C
              TO THE DRIFT TIME TO DETERMINE THE LENGTH OF TIME A
 96
              HAZARD REMAINS IN THE UNIT AREA.
 97
 98
          C
                    PRSTIM(K) = EVPTMX(K) + TDRFT
 99
          С
100
             FOR A VAPOR AGENT: CHECK AGAINST THE POSSIBILITY OF ZERO WIND.
101
              IF ZERO WIND, THE MAXIMUM PERSISTENCE TIME IS THE MAXIMUM
102
             NUSSE GRID TIME, TVPR. NTVPR IS THE NUMBER OF TOXIC VAPOR
103
              WEAPONS. SET QQQ TO THE MAXIMUM OF THE NUSSE
104
              GRID TIME OR THE EVAPORATION TIME OF A LIQUID AGENT(0 IF
105
106
              VAPOR AGENT).
107
                    IF ( NTVPR(K) .GT. 0 ) THEN
108
                QQQ = AMAX1 (EVPTMX (K), TVPR (K, NTVPR (K)))
109
110
                    ELSE
                QQQ = EVPTMX(K)
111
                    ENDIF
112
113
             SINCE BOTH PRSTIM AND QQQ ARE UPPER BOUNDS,
114
             CHOOSE THE LESSER OF THE TWO. THIS PREVENTS THE
115
             UNIT FROM STAYING IN MOPP AN INFINITE AMOUNT OF TIME
116
             AFTER A NONPERSISTENT AGENT ATTACK.
117
118
                    PRSTIM(K) = AMIN1(PRSTIM(K), QQQ)
119
120
             FINALLY, WARN USER IF PERSISTENCE TIME EXCEEDS ENCOUNTER LENGTH.
121
             TALTIM IS AN ARRAY OF RECONSTITUTION TIMES. NRECT IS NUMBER OF RECONSTITUTION TIMES.
122
123
124
                    IF ( PRSTIM(K) .GT. TALTIM(NRECT) ) THEN
125
126
                       WRITE (IM6, 69) PRSTIM(K), K, TALTIM(NRECT)
                       FORMAT (' *** WARNING *** PERSISTENCE TIME (',F10.2,
127
              69
                       ') OF TOXIC WEAPON DISPERSION # ', 14,' IS LONGER THAN',
128
                       ' ENCOUNTER TIME (',F10.2,')',/
129
                       ' ONCE INTO MOPP, PERSONNEL WILL NOT GET OUT.' )
130
                       WRITE (1,69) PRSTIM(K), K, TALTIM(NRECT)
131
132
                    ENDIF
133
             24
                    CONTINUE
                ENDIF
134
                RETURN
135
                END
136
```

APPENDIX B:

MEVATEC'S CLDTIM.f SUBROUTINE

```
SUBROUTINE CLDTIM
             THIS SUBROUTINE DEALS WITH THE PROBLEM OF VAPOR CLOUD DRIFT.
          C
             THE TIME REQUIRED FOR TOXIC VAPOR TO DRIFT ACROSS THE LONGEST LENGTH
          С
             OF THE UNIT IS CALCULATED; TIME = LENGTH OF UNIT/VELOCITY OF WIND.
             THIS TIME VALUE IS USED IN THE CALCULATION OF THE
             'PERSISTENCE TIME'. PERSISTENCE TIME IS USED HERE TO REFER
             TO THE LENGTH OF TIME THAT A TOXIC HAZARD REMAINS IN THE UNIT
 8
             AREA. PERSONNEL DO NO REVERT TO ORIGINAL MOPP POSTURE
 g
10
             UNTIL SOME TIME AFTER THE 'PERSISTENCE' TIME HAS ELAPSED.
11
12
                COMMON/CULL/LCULL(2), DEPMAX(2,2), DELMAX(50), TLEMAX
                COMMON/IO/ IM5, IM6
13
                COMMON/LTHTYP/ LCNV, LNUKE, LNUCDN, LTOX, LTOXDN, LNUCDS, LTOXDS
14
                LOGICAL LTOX
                COMMON/RECOOP/ NRECT, TIMGAP, TRECUP(20), TRECON(20)
COMMON/TALLY/ NREC, TALTIM(20), LNKWKT(20), LCHNST(20),
16
17
18
                + EFFREC (20)
               COMMON/TOXTRM/XTRC(13,2),YTRC(13,2),XTRP(13,2,2),YTRP(13,2,2),
+ XTRV(13,2,2),YTRV(13,2,2),CTMIN(13),CTMAX(13),TOXWND(13),
19
20
               + CNCXT(13), CNCX(13), CNCY(13), CNCTP(13)
21
22
                COMMON/TXCLTH/NTXWPN, NXCNTM(13), NTVPR(13), NXVPR(13), NYVPR(13),
               + NDXTX(13,4),XCNTM(13,176),TVPR(13,10),XVPR(13,300),
+ YVPR(13,99),EVPTMX(13),PRSTIM(13),NYCNTM(13),
23
24
25
                + YCNTM(13,50)
26
             DETERMINE THE DRIFT TIME OF THE TOXIC CLOUD
27
28
             AND ADD THIS TO THE PERSISTENCE TIME GIVEN BY NUSSE (TIME FOR
             AVERAGE DROPLET TO EVAPORATE.)
29
30
31
         С
             TIME FOR CLOUD TO DRIFT DOWNWIND OF UNIT IS CALCULATED BASED ON
32
         С
             THE RELATIONSHIP: DISTANCE = VELOCITY * TIME.
33
             TDRFT = MAXIMUM LENGTH OF UNIT/VELOCITY OF WIND.
34
         С
             TDRFT IS TIME FOR CLOUD TO DRIFT DOWNWIND OF UNIT.
35
36
             LTOX IS LOGICAL SIGNIFYING WHETHER OR NOT THIS IS A TOXIC SCENARIO.
37
             IF THIS IS A TOXIC SCENARIO THEN DO THE FOLLOWING CALCULATION:
38
39
                IF ( LTOX ) THEN
40
         C
41
             CALCULATE MAXIMUM LENGTH OF THE UNIT BASED ON PYTHAGOREAN THEOREOM.
             DEPMAX IS ARRAY OF MAXIMA AND MINIMA DEPLOYMENT POINTS.
42
43
             DEPMAX(1,2) IS THE MAXIMUM VALUE DEPLOYMENT POINT ALONG X AXIS.
             DEPMAX(1,1) IS THE MINIMUM VALUE ALONG THE X AXIS.
44
45
             DEPMAX(2,2) IS THE MAXIMUM VALUE ALONG THE Y AXIS.
             DEPMAX(2,1) IS THE MINIMUM VALUE ALONG THE Y AXIS.
46
47
48
            XTENTV IS THE LARGEST EXTENT OF THE CLOUD
49
50
                XMIN = 1.0E10
51
                XMAX = -1.0E10
                YMIN = 1.0E10
52
53
                YMAX = -1.0E10
54
                DO 995 K = 1,13
DO 996 J = 1,NXVPR(K)
55
56
57
                 XMIN = AMIN1(XMIN, XVPR(K, J))
                 XMAX = AMAX1(XMAX, XVPR(K, J))
58
59
         996
                CONTINUE
60
                DO 995 J = 1, NYVPR(K)
61
                 YMIN = AMIN1(YMIN, YVPR(K, J))
62
                 YMAX = AMAX1(YMAX, YVPR(K, J))
         995
                CONTINUE
63
                 XTENTV = SQRT((XMAX - XMIN)**2 +
64
65
                                 (YMAX - YMIN)**2)
66
67
            XTENT IS THE LARGEST EXTENT OF THE UNIT ACROSS WHICH
            A TOXIC CLOUD MIGHT TRAVEL
68
69
         C
70
                   XTENT = SQRT ( (DEPMAX(1,2)-DEPMAX(1,1))**2 +
                     (DEPMAX(2,2)-DEPMAX(2,1))**2)
71
```

```
XTENT IS THE GREATER OF THE DIAGONAL OF THE CLOUD VERSUS
  72
             C
                       THE DIAGONAL OF THE UNIT
  73
  74
  75
                       XTENT = AMAX1 (XTENT, XTENTV)
  76
             С
  77
                        DO 24 K = 1, 13
                        IF ( TOXWND (K) .GT. 0.01 ) THEN
  78
  79
             C
                MULTIPLY TOXWIND BY 60 TO CONVERT FROM SECONDS TO MINUTES.
                MINUTES = METERS/[(METERS/SECOND)(60 SECONDS/MINUTE)].
  81
  82
                            TDRFT = XTENT / (TOXWND(K)*60.)
  83
  84
                IF WIND SPEED IS CLOSE TO ZERO, THEN THERE IS NO DRIFT DOWNWIND,
  85
                SO TDRFT IS SET CLOSE TO INFINITE. CLOUD WON'T DRIFT DOWNWIND
  86
                AND PERSONNEL WILL BE FORCED TO STAY IN MOPP UNTIL EVAPORATION OF AGENT. THIS IS VALID FOR THE PERSISTENT AGENT CASE, BUT
  87
  88
                NOT FOR A NONPERSISTENT AGENT. A CHECK AND CORRECTION IS
 89
  90
                MADE FOR THIS LATER.
  91
  92
                        ELSE
 93
                            TDRFT = 1.E35
  94
                        ENDIF
 95
             C
                TDRFT IS THE TIME - IN MINUTES - TO DRIFT ACROSS THE
 96
                LARGEST EXTENT OF THE UNIT.
 97
 98
                PRSTIM CONTAINS THE TIME OF THE FIRST DOSAGE GRID TO SHOW NO INCREASES. FOR A PURE LIQUID (NO VAPOR) IT IS 0.
 99
100
                IF EVERY GRID SHOWED AN INCREASE, IT IS 1.E35. (THE AURA ANALYST MUST BE CAREFUL WHEN CHOOSING NUSSE INPUT TIMES TO AVOID MODELING AN 'INFINETELY' PERSISTENT
101
102
103
                HAZARD AS A RESULT OF SELECTING TIMES WHICH ARE
104
                NOT REPRESENTATIVE OF THE LIFETIME OF THE HAZARD.
105
106
                TOTAL PERSISTENCE TIME IS ESTIMATED BY TAKING THIS
107
            C
                MAXIMUM EVAPORATION TIME AND ADDING THE DRIFT TIME TO IT TO ACCOUNT FOR THE SECONDARY EVAPORATION HAZARD OF LIQUID
108
109
                AGENT. HOWEVER, THERE IS NO SECONDARY VAPOR HAZARD FOR PURELY
110
            C
111
                VAPOR AGENTS.
            С
112
                TO CALCULATE TOTAL PERSISTENCE TIME....
            С
113
114
                FOR A LIQUID AGENT:
115
            С
116
            С
                ADD EVPTMX, THE EVAPORATION TIME OF A LIQUID AGENT,
                TO THE DRIFT TIME TO DETERMINE THE LENGTH OF TIME A
            С
117
                HAZARD REMAINS IN THE UNIT AREA.
118
            C
119
                       PRSTIM(K) = EVPTMX(K) + TDRFT
120
121
                FOR A VAPOR AGENT: CHECK AGAINST THE POSSIBILITY OF ZERO WIND. IF ZERO WIND, THE MAXIMUM PERSISTENCE TIME IS THE MAXIMUM
122
123
                NUSSE GRID TIME, TVPR. NTVPR IS THE NUMBER OF TOXIC VAPOR WEAPONS. SET QQQ TO THE MAXIMUM OF THE NUSSE
124
125
126
            С
                GRID TIME OR THE EVAPORATION TIME OF A LIQUID AGENT (O IF
                VAPOR AGENT).
127
128
                   IF ( NTVPR(K) .GT. 0 ) THEN
QQQ = AMAX1(EVPTMX(K), TVPR(K,NTVPR(K)))
129
130
131
                       ELSE
                   QQQ = EVPTMX(K)
132
133
                       ENDIF
134
                SINCE BOTH PRSTIM AND QQQ ARE UPPER BOUNDS,
135
                CHOOSE THE LESSER OF THE TWO. THIS PREVENTS THE UNIT FROM STAYING IN MOPP AN INFINITE AMOUNT OF TIME
136
137
                AFTER A NONPERSISTENT AGENT ATTACK.
138
139
            С
140
                       PRSTIM(K) = AMIN1(PRSTIM(K), QQQ)
141
              FINALLY, WARN USER IF PERSISTENCE TIME EXCEEDS ENCOUNTER LENGTH.
142
```

```
143
                            TALTIM IS AN ARRAY OF RECONSTITUTION TIMES.
144
                     С
                            NRECT IS NUMBER OF RECONSTITUTION TIMES.
                     č
145
                                         IF( PRSTIM(K) .GT. TALTIM(NRECT) ) THEN
    WRITE(IM6,69) PRSTIM(K), K, TALTIM(NRECT)
    FORMAT('0*** WARNING *** PERSISTENCE TIME (',F10.2,
    ') OF TOXIC WEAPON DISPERSION # ',I4,' IS LONGER THAN',
    ' ENCOUNTER TIME (',F10.2,')',/
    ' ONCE INTO MOPP, PERSONNEL WILL NOT GET OUT.')
    WRITE(1,69) PRSTIM(K), K, TALTIM(NRECT)

ENDIE
146
147
148
                             69
149
150
151
152
153
                                         ENDIF
154
                                        CONTINUE
                                  ENDIF
155
156
                                  RETURN
157
                                  END
```

NO. OF <u>COPIES</u> <u>ORGANIZATION</u>

- 2 DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
- 1 DIRECTOR
 US ARMY RESEARCH LAB
 ATTN AMSRL OP SD TA
 2800 POWDER MILL RD
 ADELPHI MD 20783-1145
- 3 DIRECTOR
 US ARMY RESEARCH LAB
 ATTN AMSRL OP SD TL
 2800 POWDER MILL RD
 ADELPHI MD 20783-1145
- 1 DIRECTOR
 US ARMY RESEARCH LAB
 ATTN AMSRL OP SD TP
 2800 POWDER MILL RD
 ADELPHI MD 20783-1145

ABERDEEN PROVING GROUND

5 DIR USARL ATTN AMSRL OP AP L (305)

NO. OF NO. OF COPIES ORGANIZATION COPIES ORGANIZATION ARMY RESEARCH LABORATORY OSD OUSD AT 1 1 ATTN AMSRL ST STRT TAC SYS DR FRASIER ATTN DR SCHNEITER 2800 POWDER MILL RD 3090 DEFNS PENTAGON RM 3E130 ADELPHI MD 20783-1197 WASHINGTON DC 20301-3090 ARMY RESEARCH LABORATORY 1 ODDRE AT ACOUISITION AND TECH ATTN AMSRL SL. DR WADE ATTN DR GONTAREK WSMR NM 88002-5513 3080 DEFENSE PENTAGON WASHINGTON DC 20310-3080 ARMY RESEARCH LABORATORY ASST SECY ARMY RESEARCH ATTN AMSRL SLE 1 MR MARES DEVELOPMENT ACQUISITION ATTN SARD ZD RM 2E673 WSMR NM 88002-5513 103 ARMY PENTAGON WASHINGTON DC 20310-0103 ARMY TRADOC ANL CTR 1 ATTN ATRC W ASST SECY ARMY RESEARCH MR KEINTZ DEVELOPMENT ACQUISITION WSMR NM 88002-5502 ATTN SARD ZP RM 2E661 ARMY TRNG & DOCTRINE CMND 103 ARMY PENTAGON 1 ATTN ATCD B WASHINGTON DC 20310-0103 FT MONROE VA 23651 ASST SECY ARMY RESEARCH 1 ABERDEEN PROVING GROUND DEVELOPMENT ACQUISITION ATTN SARD ZS RM 3E448 103 ARMY PENTAGON CDR USATECOM WASHINGTON DC 20310-0103 ATTN: AMSTE-TA ASST SECY ARMY RESEARCH CDR USAMSAA 2 1 DEVELOPMENT ACQUISITION ATTN: AMXSY-ST ATTN SARD ZT RM 3E374 AMXSY-D 103 ARMY PENTAGON WASHINGTON DC 20310-0103 DIR USARL ATTN: AMSRL-SL, J WADE (433) UNDER SEC OF THE ARMY AMSRL-SL-I, M STARKS (433) ATTN DUSA OR AMSRL-SL-C, W HUGHES (E3331) AMSRL-SL-B, P DEITZ (328) RM 2E660 **102 ARMY PENTAGON** CDR CBDCOM WASHINGTON DC 20310-0102 ATTN: TECHNICAL LIBRARY ASST DEP CHIEF OF STAFF **BLDG E3330** OPERATIONS AND PLANS DIR CBIAC ATTN DAMO FDZ RM 3A522 1 BLDG E3330, RM 150 **460 ARMY PENTAGON** WASHINGTON DC 20310-0460

DEPUTY CHIEF OF STAFF

OPERATIONS AND PLANS ATTN DAMO SW RM 3C630 400 ARMY PENTAGON WASHINGTON DC 20310-0400

1

NO. OF

COPIES ORGANIZATION

- 5 CORPS SAM PROJECT MANAGEMENT OFC ATTN SFAE MD MR GENE PRESTON PO BOX 1500 HUNTSVILLE AL 35807-3801
- 2 CORPS SAM PROJECT MANAGEMENT OFC ATTN SFAE MD MS ELIZABETH SCONIERS PO BOX 1500 HUNTSVILLE AL 35807-3801
- 5 MEVATEC CORPORATION
 ATTN MR JOE ANDRZEJEWSKI
 1525 PERIMETER PARKWAY
 SUITE 500
 HUNTSVILLE AL 35806

ABERDEEN PROVING GROUND, MD

18 DIR, USARL

ATTN: AMSRL-SL-B,

J. KLOPCIC (328)

AMSRL-SL-BL,

S. JUARASCIO (328)

M. KUNKEL (328)

B. STEELMAN (328)

M. RITONDO (328)

AMSRL-SL-CS,

M. SMITH (E3331)

J. KELLY (E3331)

AMSRL-SL-CM,

D. FARENWALD (E3331)

R. ZUM BRUNNEN (10 CPS) (E3331)

USER EVALUATION SHEET/CHANGE OF ADDRESS This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts. 1. ARL Report Number <u>ARL-TR-978</u> Date of Report <u>March 1996</u> 2. Date Report Received _____ 3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) 4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) 5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. 6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) Organization **CURRENT** Name ADDRESS Street or P.O. Box No. City, State, Zip Code 7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

Organization Name OLD **ADDRESS** Street or P.O. Box No. City, State, Zip Code

> (Remove this sheet, fold as indicated, tape closed, and mail.) (DO NOT STAPLE)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS



FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
U.S. ARMY RESEARCH LABORATORY
ATTN: AMSRL-SL-CM
ABERDEEN PROVING GROUND, MD 21010-5423

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES